

NEOLITH

600

BRICK AND TERRACOTTA CLEANER

WHAT THE PRODUCT DOES.

NEOLITH 600 is a cleaner formulated for the removal of dirt, carbon, algae, rust stains from brick work and terracotta.

PRODUCT DESCRIPTION

NEOLITH 600 is a pink aqueous liquid, it is corrosive and contains Hydrofluoric Acid (UN1790) (less than 10%). When adequately diluted the organic materials are completely biodegradable. This formulation has been in use for over 30 years.

SAFE HANDLING

At any time when this product is being transported, or being used, persons handling or carrying the product should have available a drum of clean water for use in emergencies and HYDROFLUORIC ACID ANTEDOTE GEL for immediate treatment of accidental splashes or burns. Containers must be stored in a safe place with caps secured, and a trained responsible person(s) detailed for security in depots, in transit and on site. Only competent persons should handle this product.

PRE CLEANING RECOMMENDATIONS

The masonry may require degreasing before application of NEOLITH 600*.

*Where this asterisk appears users should consult our document GENERAL THECHIQUES AND MATERIALS FOR THE CLEANING OF MASONRY USING NEOLITH CHEMICALS for further details and information.

HOW TO USE THE PRODUCT

Establish the method and contact time, and dilution of NEOLITH 600 by a test patch*. Using a fibre bristle brush work the product into the pre-wetted surface, starting at the top and working to natural breaks. A normal contact time of 5-15 minutes is desirable and dilutions of NEOLITH 600 if the performance is satisfactory. In this respect a degreasing increases the efficiency of the acid and often permits greater dilution of the cleaner. Pressure water jetting, using hot or cold water, should take 3 minutes/m² to remove the surface debris.

FLOWPLANT GROUP
LEADERS IN CLEANING TECHNOLOGY
Gemini House, Brunel Road, Churchfields Industrial Estate
Salisbury, Wiltshire SP2 7PU



COVERAGE

Approximately 3-4m²/l.

MATERIALS TO BE AVOIDED

Glass, polished granite, glazed aluminium, zinc, bronze, brass, copper and lead*. The verification of any colouration changes should be observed during test trial work. Alternatively the NEOLITH LONG CONTACT METHOD can be used*.

The product is not suitable for use on limestone, Portland stone, Bath stone, marble, slate or calcited materials.

PROTECTION OF OPERATIVES

Chemical protection suits are needed along with PVC gauntlet gloves, face shields. head cover and also suitable footwear. A bucket of clean water for emergency use should be to hand. Nobody must be allowed to pass underneath or work under cleaning areas. Spillages must be washed down immediately. At the end of the work period wash down all equipment eg. scaffolding and boards. A Hydrofluoric burns kit should be at hand for the treatment of any acid burns. Only experienced operatives should handle this product. (See treatment Sheet).

FIRST AID

See the full instructions given in the COSHH Data sheet.

ECOLOGY

When diluted the organic ingredients are all biodegradable. Effluent, if washed into soil will break down rapidly. If the product is inadvertently sprayed onto plants/vegetation it should be rinsed off. Rinsing with water will prevent permanent damage to plants. Plastic sheeting could be used to protect such plant life. Using the NEOLITH ENVIRONMENTAL JETTING TECHNIQUE* maximum dilution of the chemical is achieved and no damage has been found to fish when such debris enters rivers and streams but contractors are advised to consult the appropriate authorities before disposal of water waste debris.

DISPOSAL OF CONTAINERS

When empty the containers should be filled with water and then emptied and disposed in an approved manner.